

DELTA ^{RGB} DDR5

Gaming Desktop Memory



DELTA RGB DDR5

DELTA RGB DDR5

With a refreshing visual experience modeled after a stealth aircraft, the T-FORCE DELTA RGB DDR5 offers a 120°Ultra-Wide Lighting angle that supports lighting software from various manufacturers. In addition to support the latest Intel XMP3.0 one-click OC technology, the DELTA RGB DDR5 is also equipped with PMIC and on-die ECC to ensure stable, efficient power distribution across all components for system stability and performance.

Main Feature

- RGB Colors & 120°Ultra-Wide Lighting
- Supports Intel XMP3.0 for One-Click Overclocking
- Power Management IC (PMIC) Equipped for Stable, Efficient Power Usage
- Strengthened PMIC Cooling Design
- On-die ECC for Stable System
- High-Quality ICs Selected for Stability & Reliability
- Equipped with Smart RGB IC Controller that Supports Various Lighting Effect Software



Specification

Module Type	DDR5 288 Pin Non-ECC Unbuffered DIMM				
Frequency	7200	6600	6400	6200	6000
Capacity	16GBx2	16GBx2	16GB 16GBx2	16GB 16GBx2	16GB 16GBx2
Latency	34-42-42-84	34-40-40-84	40-40-40-84	38-38-38-78	38-38-38-78
Data Transfer Bandwidth	57,600 MB/s (PC5-57600)	52,800 MB/s (PC5 52800)	51,200 MB/s (PC5 51200)	49,600 MB/s (PC5 49600)	48,000 MB/s (PC5 48000)
Voltage	1.4V	1.4V	1.35V	1.25V	1.25V
Compatibility		Intel: 600 series			
Dimensions	46.1(H) x 144.2(L) x 7(W)mm				
Warranty	Lifetime warranty				

Specification

Module Type	DDR5 288 Pin Non-ECC Unbuffered DIMM				
Frequency	6000	5600	5600	5600	5200
Capacity	16GB 16GBx2	16GB 16GBx2	16GB 16GBx2	16GB 16GBx2	16GB 16GBx2
Latency	30-36-36-76	32-36-36-76	36-36-36-76	40-40-40-84	40-40-40-76
Data Transfer Bandwidth	48,000 MB/s (PC5 48000)	44,800 MB/s (PC5 44800)	44,800 MB/s (PC5 44800)	44,800 MB/s (PC5 44800)	41,600 MB/s (PC5 41600)
Voltage	1.35V	1.2V	1.2V	1.2V	1.25V
Compatibility	Intel: 600 series				
Dimensions	46.1(H) x 144.2(L) x 7(W)mm				
Warranty	Lifetime warranty				

Ordering Information

Color	Frequency	CAS Latency/Voltage	Capacity	IC Specifications	Team P/N
BLACK	DDR5-5200 (PC5-41600)	CL40-40-40-76 1.25V	16GB	x8	FF3D516G5200HC40C01
		CL32-36-36-76 1.2V	16GB	x8	FF3D516G5600HC3201
	DDR5-5600 (PC5-44800)	CL36-36-36-76 1.2V	16GB	x8	FF3D516G5600HC36B01
		CL40-40-40-84 1.2V	16GB	x8	FF3D516G5600HC40B01
	DDR5-6000 (PC5-48000)	CL30-36-36-76 1.35V	16GB	x8	FF3D516G6000HC3001
		CL38-38-38-78 1.25V	16GB	x8	FF3D516G6000HC38A01
	DDR5-6200 (PC5-49600)	CL38-38-38-78 1.25V	16GB	x8	FF3D516G6200HC38A01
	DDR5-6400 (PC5-51200)	CL40-40-40-84 1.35V	16GB	x8	FF3D516G6400HC40B01

Color	Frequency	CAS Latency/Voltage	Capacity	IC Specifications	Team P/N
WHITE	DDR5-5200 (PC5-41600)	CL40-40-40-76 1.25V	16GB	x8	FF4D516G5200HC40C01
		CL32-36-36-76 1.2V	16GB	x8	FF4D516G5600HC3201
	DDR5-5600 (PC5-44800)	CL36-36-36-76 1.2V	16GB	x8	FF4D516G5600HC36B01
		CL40-40-40-84 1.2V	16GB	x8	FF4D516G5600HC40B01
	DDR5-6000 (PC5-48000)	CL30-36-36-76 1.35V	16GB	x8	FF4D516G6000HC3001
		CL38-38-38-78 1.25V	16GB	x8	FF4D516G6000HC38A01
	DDR5-6200 (PC5-49600)	CL38-38-38-78 1.25V	16GB	x8	FF4D516G6200HC38A01
	DDR5-6400 (PC5-51200)	CL40-40-40-84 1.35V	16GB	x8	FF4D516G6400HC40B01

Color	Frequency	CAS Latency/Voltage	Capacity	IC Specifications	Team P/N
BLACK	DDR5-5200 (PC5-41600)	CL40-40-40-76 1.25V	16GBx2	x8	FF3D532G5200HC40CDC01
		CL32-36-36-76 1.2V	16GBx2	x8	FF3D532G5600HC32DC01
	DDR5-5600 (PC5-44800)	CL36-36-36-76 1.2V	16GBx2	x8	FF3D532G5600HC36BDC01
		CL40-40-40-84 1.2V	16GBx2	x8	FF3D532G5600HC40BDC01
	DDR5-6000 (PC5-48000)	CL30-36-36-76 1.35V	16GBx2	x8	FF3D532G6000HC30DC01
		CL38-38-38-78 1.25V	16GBx2	x8	FF3D532G6000HC38ADC01
	DDR5-6200 (PC5-49600)	CL38-38-38-78 1.25V	16GBx2	x8	FF3D532G6200HC38ADC01
	DDR5-6400 (PC5-51200)	CL40-40-40-84 1.35V	16GBx2	x8	FF3D532G6400HC40BDC01
DDR5-6600 (PC5-52800)	CL34-40-40-84 1.4V	16GBx2	x8	FF3D532G6600HC34DC01	
DDR5-7200 (PC5-57600)	CL34-42-42-84 1.4V	16GBx2	x8	FF3D532G7200HC34ADC01	

Color	Frequency	CAS Latency/Voltage	Capacity	IC Specifications	Team P/N
WHITE	DDR5-5200 (PC5-41600)	CL40-40-40-76 1.25V	16GBx2	x8	FF4D532G5200HC40CDC01
		CL32-36-36-76 1.2V	16GBx2	x8	FF4D532G5600HC32DC01
	DDR5-5600 (PC5-44800)	CL36-36-36-76 1.2V	16GBx2	x8	FF4D532G5600HC36BDC01
		CL40-40-40-84 1.2V	16GBx2	x8	FF4D532G5600HC40BDC01
	DDR5-6000 (PC5-48000)	CL30-36-36-76 1.35V	16GBx2	x8	FF4D532G6000HC30DC01
		CL38-38-38-78 1.25V	16GBx2	x8	FF4D532G6000HC38ADC01
	DDR5-6200 (PC5-49600)	CL38-38-38-78 1.25V	16GBx2	x8	FF4D532G6200HC38ADC01
	DDR5-6400 (PC5-51200)	CL40-40-40-84 1.35V	16GBx2	x8	FF4D532G6400HC40BDC01
DDR5-6600 (PC5-52800)	CL34-40-40-84 1.4V	16GBx2	x8	FF4D532G6600HC34DC01	
DDR5-7200 (PC5-57600)	CL34-42-42-84 1.4V	16GBx2	x8	FF4D532G7200HC34ADC01	

※The frequency and stability of the overclocking memory when automatic reading of the overclocking value [XMP or D.O.C.P] is turned on will vary depending on the difference between the motherboard and CPU. Check "Product Compatibility Inquiry" before purchase for further info <https://www.teamgroupinc.com/en/support/compatibility.php>

※We reserve the right to modify product specifications without prior notice.